

C SERIES ORDER DATA

SERIES

C	SINGLE ROD END
DC	DOUBLE ROD END
CSR	SINGLE ROD END SPRING RETURN
CSE	SINGLE ROD END SPRING EXTEND
DCSR	DOUBLE ROD END SPRING RETURN

STANDARD STROKES

BORE	BORE	BORE	BORE	BORE	BORE	BORE
1/2	3/4	1 1/8	1 5/8	2.00	2 1/2	3.00
.062	.125	.125	.125	.125	.125	.125
.125	.187	.250	.250	.250	.250	.250
.250	.250	.375	.500	.375	.500	.500
.375	.375	.500	.750	.500	.750	.750
.500	.500	.750	1.00	.750	1.00	1.00
.625	.625	1.00	1.50	1.00	1.50	1.50
.750	.750	1.25	2.00	1.50	2.00	2.00
1.00	1.00	1.50	3.00	2.00	3.00	3.00
1.25	1.25	1.75	4.00	3.00	4.00	4.00
1.50	1.50	2.00		4.00		
2.00	2.00	3.00				
3.00	3.00	4.00				
4.00	4.00					

MOUNTS
 CLEVIS MOUNT AND PIN CM&P
 ROD CLEVIS AND PIN RC&P

C 1 1/8 X 4.00

BORE SIZE

BORE CODE	BORE INCHES	AREA EXTEND	AREA RETRACT
1/2	.500	.19	.14
3/4	.750	.44	.37
1 1/8	1.125	.99	.80
1 5/8	1.625	2.0	1.76
2.00	2.000	3.14	2.70
2 1/2	2.500	4.91	4.47
3.00	3.000	7.07	6.62
4.00	4.000	12.57	11.97

V

OPTIONS

VITON SEALS	V
MALE ROD END	MR
NON-ROTATING	NR
CHROME ROD	CR
BUMPER ROD END	BR
BUMPER BLIND END	BB
BUMPER ROD AND BLIND	BR&BB

CM&P

OPTIONS TO BE SPELLED OUT
 ROD EXTENSION
 SPECIAL ROD THREAD

ROD EXT 1.00